

## In the Claims

---

Claim 1 (original): A method for conditioning a surface of a polishing pad after chemical-mechanical polishing of a semiconductor substrate with the pad surface, comprising exposing the pad surface to steam.

31 Claim 2 (original): The method of claim 1 wherein the steam is jetted onto the pad surface to impact the surface with a pressure of from about 10 psig to about 20 psig.

EV372453511 Claim 3 (original): The method of claim 1 wherein the steam has a temperature of at least about 200°F as it impacts the surface.

Claim 4 (original): The method of claim 1 wherein the steam is jetted onto the pad surface from a head which is displaced relative to the pad surface during the exposure of the pad surface to the steam.

Claim 5 (original): The method of claim 1 wherein the pad has a contaminant associated therewith prior to the conditioning, and wherein a chemical agent suitable for reacting with the contaminant is within the steam during the exposure of the pad surface to the steam.

Claim 6 (original): The method of claim 1 wherein ammonium is within the steam during the exposure of the pad surface to the steam.

Claim 7 (original): The method of claim 1 wherein ammonium citrate is within the steam during the exposure of the pad surface to the steam.

31  
cont  
Claim 8 (original): The method of claim 1 wherein the chemical-mechanical polishing utilizes the pad to polish a copper-containing material; and wherein ammonium is within the steam during the exposure of the pad surface to the steam.

EV372453511  
Claim 9 (original): The method of claim 1 wherein the pad is rubbed against a conditioning stone during the exposure to the steam.

Claim 10 (original): The method of claim 1 wherein the pad is rubbed against a conditioning stone prior to the exposure to the steam.

Claim 11 (original): The method of claim 1 wherein the pad is rubbed against a conditioning stone after the exposure to the steam.

Claims 12-35 (canceled).

---